



Starpatch Concrete Products

#5 -6420 Beresford Street,

Burnaby, B.C. V5E 1B6

Phone: (604) 433-7355 Fax: (604) 433-7358

Quick Water Stop

Description: Formulated to temporarily divert water away from work area, patching or plugging holes and to stop seeping water on concrete surfaces. Product is produced in concrete grey with special additives to ensure the material is easy to work with and is fast drying with superior bonding.

Recommended For:

- Stopping running water or seepage at defects or joints in concrete manholes, sewer pipes basement walls or any concrete or masonry surface with water penetration.
- Stopping water seepage around manholes.
- Damming 1" to 4" around manholes, etc.
- Patching or plugging holes.

Advantages:

- Fast drying.
- Easy to use in dry form for damming.
- Just add water to plug holes.
- Superior bonding and adhesion properties.

Mixing Instructions: Wear Rubber Gloves

- **To dam around manholes and stop water seepage:** Pile mixture around the area to be kept free of water from 1" to 4" high, depending on water seepage.
- **To plug holes:** Mix 4 parts powder to 1 part clean water. Mix to a stiff paste consistency in container using pointer trowel. Final mixing should be done by hand, press the mixed mortar by hand into the opening. Hold in place until product begins to set, in about 2-3 minutes.

Setting Time: Initial set of in 2 to 3 minutes. Rapidly gains compressive strength within a few hours.

Application: To plug holes, square cut with a chisel to a minimum of 3/4" depth. Remove all loose material from the area to be repaired. Apply *Quick Water Stop* with a pointer trowel or with hands to fill the crack.

To stop active streams of water coming from a crack start by pushing *Quick Water Stop* into the crack at the top of the crack and holding it

in place until it sets. Repeat this until the entire crack is filled to the bottom of the crack.

Limitations: Temperature at the time of application of this mortar may not be lower than 5°C/41°F. In hot weather use cold water to slow set up time. Do not mix more material that can be used within 1-2 minutes.

Bucket Life: 2 minutes.

Shelf Life: One year in the original unopened bag if kept in dry storage.

Packaging: 4.54kg/10lbs. or 22.7kg/50lbs pail.

Caution: Contains cement, a polymer and other additives which may cause skin irritation. In case of skin or eye contact, wash thoroughly with water. Please consult the MSDS for detailed safety and handling instructions. In case of eye contact consult with nearest physician. **KEEP OUT OF REACH OF CHILDREN.**

Warranty: Starpatch Concrete Products warrants that if its products prove to have manufacturing defects and Starpatch is notified of such within 6 months from date of Starpatch shipping, Starpatch will replace the defective products F.O.B. factory. Such product replacement shall constitute the sole and exclusive remedy for any claim under this warranty. This warranty is in lieu of all other warranties, expressed, implied or statutory and is strictly limited to its terms. Starpatch makes no warranty of merchantability or suitability of its products for any particular purpose. Starpatch sells its products upon the condition that the customers shall conduct their own tests to determine the suitability of the products for the customers intended purposes. Under no circumstances will Starpatch be liable for economic, special, incidental or consequential damages or losses of any kind whatsoever arising out of or occasioned by the selection, use, installation or replacement of this product.

Starpatch Concrete Products, Burnaby, BC.

Phone (604) 433-7355